

Synthex Primus Elite Euro
SAE 5W-30 Full Synthetic Motor Oil
ACEA C3-16, API SN

Product Description

Synthex Primus Elite Euro SAE 5W-30 Full Synthetic Motor Oil ACEA C3-16, API SN is formulated with synthetic base oils and a premium additive package. This oil is designed for use in carbureted, fuel injected, turbocharged and supercharged gasoline engines. This oil exceeds the performance requirements of API SN and ACEA C3.

Typical Properties*

SAE J300 Viscosity Grade	5W-30
Appearance, Visual	Amber, Transparent, Liquid
Viscosity @ 40°C, cSt, ASTM D445	68.0
Viscosity @ 100°C, cSt, ASTM D445	11.5
Viscosity Index, ASTM D2270	165
CCS Apparent Viscosity, cP, ASTM D5293	5,300@-30°C
MRV Apparent Viscosity, cP, ASTM D4684	22,000@-35°C
Flash Point, °C, ASTM D92	210
Pour Point, °C, ASTM D97	-42
Sulfated Ash, wt%, ASTM D874	≤ 0.8

**The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.*

Exceeds Performance Requirements

API SN
 ACEA C3-16
 BMW LL-04
 MB 229.31/229.51
 GM dexos 2

Product Code

SPE008

