

**Synthex Primus Elite**  
**SAE 5W-40; SAE 5W-50**  
**Full Synthetic Motor Oil, API SP**

**Product Description**

**Synthex Primus Elite SAE 5W-40 and 5W-50** are premium full synthetic motor oils manufactured for use in modern gasoline engines which require API SP or API SN performance.

These oils are formulated with synthetic base oils and a premium performance additive package which is specially formulated to protect high compression gasoline direct injection engines delivering superior oxidative stability, deposit control, low speed pre-ignition mitigation and timing chain wear protection.

**Typical Properties\***

<b>SAE J300 Viscosity Grade</b>	<b>5W-40</b>	<b>5W-50</b>
Appearance, Visual	Amber, Transparent, Liquid	
Viscosity @ 40°C, cSt, ASTM D445	86.8	115
Viscosity @ 100°C, cSt, ASTM D445	14.5	18.5
Viscosity Index, ASTM D2270	175	180
CCS Apparent Viscosity, cP, ASTM D5293	5,400@-30°C	5,800@-30°C
MRV Apparent Viscosity, cP, ASTM D4684	22,000@-35°C	23,000@-35°C
Flash Point, °C, ASTM D92	215	215
Pour Point, °C, ASTM D97	-42	-42

*\*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.*

**Exceeds Performance Requirements**

API SP, API SN Plus, API SN

**Product Code**

**SAE 5W-40** – SPE006

**SAE 5W-50** – SPE007

