

**Synthex Probus Elite  
Synthetic EP Gear Oils  
ISO VG 68, 100, 150, 220, 320, 460**

**Product Description**

**Synthex Probus Elite Synthetic EP Gear Oils** are premium full synthetic multi-functional gear lubricants formulated for outstanding performance in applications which require a compounded synthetic extreme pressure oil. Available in the ISO 68, 100, 150, 220, 320, and 460 viscosity grades, **Synthex Probus Elite** oils are formulated with the use of synthetic API Group III, Group IV, and Group V base stocks. The result is an optimal combination of adequate film strength across all temperatures with excellent fluidity at low temperatures and outstanding oxidative stability. A comprehensive additive package which includes extreme pressure agents, anti-oxidants, metal passivators, demulsifiers, and defoamer ensures performance in even the most demanding settings.

**Typical Properties\***

<b>ISO VG</b>	<b>68</b>	<b>100</b>	<b>150</b>	<b>220</b>	<b>320</b>	<b>460</b>
Appearance, Visual	Yellow, Transparent, Liquid					
AGMA VG	2EP	3EP	4EP	5EP	6EP	7EP
Viscosity @ 40°C, cSt, ASTM D445	68	100	150	220	320	460
Viscosity @ 100°C, cSt, ASTM D445	11.57	15.58	21.15	28.2	38.34	51.57
Viscosity Index, ASTM D2270	165	165	165	165	170	175
Flash Point, °C, ASTM D92	225	225	225	225	225	225
Pour Point, °C, ASTM D97	-50	-48	-48	-48	-45	-45

*\*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.*

**Suitable for Use:**

AIST 224, David Brown S1.53.101 (E), AGMA 9005-E02

**Product Codes:**

ISO 68 – SPE650  
ISO 220 – SPE653

ISO 100 – SPE651  
ISO 320 – SPE654

ISO 150 – SPE652  
ISO 460 – SPE655

