

***Synthex Probus  
Spindle Oils  
ISO VG 10, 15 & 22***

**Product Description**

**SYNTHEX PROBUS SPINDLE OILS ISO VG 10, 15, and 22** are premium quality lubricants designed for use in high-speed spindle bearings or any application which requires a low viscosity oil with good anti-wear and anti-oxidant properties. **SYNTHEX PROBUS SPINDE OILS** are formulated with highly refined paraffinic base stocks and a premium performance additive package which includes anti-wear, anti-oxidant, anti-foam, and demulsifying agents.

**Typical Properties\***

<b>ISO VG</b>	<b>10</b>	<b>15</b>	<b>22</b>
Appearance, Visual	Clear or Yellow, Transparent, Liquid		
Viscosity @ 40°C, cSt, ASTM D445	10.0	15.0	22.0
Viscosity @ 100°C, cSt, ASTM D445	2.57	3.4	4.37
Viscosity Index, ASTM D2270	79	95	105
Flash Point, °C, ASTM D92	170	180	195
Pour Point, °C, ASTM D97	-15	-15	-15

*\*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.*

**Product Codes:**

ISO 10 – SXP662  
ISO 100 – SXP663  
ISO 150 – SXP664

