

**Synthex Probus  
Way Lube  
ISO VG 68 & 220**

**Product Description**

**Synthex Probus Way Lube ISO VG 68 and ISO VG 220** are premium quality slideway lubricants manufactured with highly refined paraffinic base stocks and a performance additive package. **Synthex Probus Way Lubes** provide good extreme pressure protection while providing the necessary tackiness to adhere to slides and ways. The comprehensive additive package also contains anti-wear, anti-oxidant and anti-foam agents.

**Typical Properties\***

<b>ISO VG</b>	<b>68</b>	<b>220</b>
Appearance, Visual	Yellow, Transparent, Liquid	
Viscosity @ 40°C, cSt, ASTM D445	68.0	220.0
Viscosity @ 100°C, cSt, ASTM D445	8.97	20.1
Viscosity Index, ASTM D2270	105	105
Flash Point, °C, ASTM D92	215	235
Pour Point, °C, ASTM D97	-20	-15

*\*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.*

**Suitable for Use:**

Cincinnati Machine P-47 (ISO 68)  
Cincinnati Machine P-50 (ISO 220)

**Product Codes:**

ISO VG 68 – SXP665  
ISO VG 220 – SXP667

