

Synthex Teres EliteFull Synthetic Motor Oil; SAE OW-20
API SN. ILSAC GF-5

Product Description

Synthex Teres Elite Full Synthetic Motor Oils, SAE OW-20, API SN, ILSAC GF-5 is formulated with synthetic base oils and a premium additive package. This oil is designed for use in carbureted, fuel injected, turbocharged gasoline engines. This oil exceeds the performance requirements of API SN and ILSAC GF-5.

Typical Properties*

SAE J300 Viscosity Grade **OW-20 Appearance** Amber, Transparent Liquid Viscosity @ 40°C, cSt, ASTM D445 44.55 Viscosity @ 100°C, cSt, ASTM D445 8.3 Viscosity Index, ASTM D2270 165 CCS Apparent Viscosity, cP, ASTM D5293 5,400@-35°C MRV Apparent Viscosity, cP, ASTM D4684 22,000@-40°C Flash Point, °C, ASTM D92 215 Pour Point, °C, ASTM D97 -48

Exceeds Performance Requirements

API SN with Resource Conserving, API SM, API SL, API SJ ILSAC GF-5 Chrysler MS6395 Ford WSS-M2C947-A

Product Code: STE100



^{*}The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.