

**Synthex Frictio 4T (Four Stroke)
Full Synthetic Engine Oil
SAE 5W-40, 10W-40, 10W-50 API SN, JASO MA2**

Product Description

Synthex Frictio Full Synthetic Engine Oils 4T (Four-Stroke) are full synthetic, super high-performance, multi-grade lubricants for use in high-RPM, 4-stroke motorcycle engines with integral gear boxes and wet clutches as well as for use in any application requiring a four-stroke engine oil meeting the requirements of JASO MA2, JASO MA or API SN. Blended with 100% synthetic basestocks and premium performance additives, **Synthex Frictio Full Synthetic Engine Oils 4T (Four-Stroke)** provide excellent protection during rapid RPM increase. Specialty friction modifiers provide for smooth clutch and gear shift operation while specialty anti-oxidants and sophisticated dispersant technology provide enhanced cleanliness. **Synthex Frictio Full Synthetic Engine Oils 4T (Four-Stroke)** are highly shear stable therefore eliminating viscosity breakdown. These products are full synthetic multi-grade engine oils suitable for use in all seasons.

Typical Properties*

SAE J300 Viscosity Grade	5W-40	10W-40	10W-50
Appearance, Visual	Amber, Transparent, Liquid		
Viscosity @ 40°C, cSt, ASTM D445	84.5	89.2	107.65
Viscosity @ 100°C, cSt, ASTM D445	14.5	14.5	17.5
Viscosity Index, ASTM D2270	180	170	180
CCS Apparent Viscosity, cP, ASTM D5293	6,000@-30°C	5,800@-25°C	6,500@-25°C
MRV Apparent Viscosity, cP, ASTM D4684	24,000@-35°C	19,000@-30°C	23,000@-30°C
Flash Point, °C, ASTM D92	215	215	215
Pour Point, °C, ASTM D97	-42	-40	-40

**The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.*

Suitable for Use:

API SN, JASO MA2, JASO MA

Product Codes:

SAE 5W-40 – SFE090
SAE 10W-40 – SFE091
SAE 10W-50 – SFE093

